

globus rsl  
7.2

Generated by Doxygen 1.7.4

Thu May 5 2011 06:59:27

## Contents

<b>1</b>	<b>Main Page</b>	<b>1</b>
<b>2</b>	<b>Module Index</b>	<b>2</b>
2.1	Modules . . . . .	2
<b>3</b>	<b>Module Documentation</b>	<b>2</b>
3.1	RSL Predicates . . . . .	2
3.1.1	Detailed Description . . . . .	2
3.1.2	Function Documentation . . . . .	2
3.2	RSL Constructors . . . . .	6
3.2.1	Function Documentation . . . . .	7
3.3	RSL Memory Management . . . . .	9
3.3.1	Function Documentation . . . . .	9
3.4	RSL Accessor Functions . . . . .	12
3.4.1	Function Documentation . . . . .	12
3.5	List Functions . . . . .	17
3.5.1	Function Documentation . . . . .	17
3.6	RSL Value Accessors . . . . .	17
3.6.1	Function Documentation . . . . .	18
3.7	RSL Display . . . . .	20
3.7.1	Function Documentation . . . . .	20
3.8	RSL Parsing . . . . .	21
3.8.1	Function Documentation . . . . .	21

## 1 Main Page

The Globus RSL library is provides the following functionality:

- [RSL Predicates](#)
- [RSL Constructors](#)
- [RSL Memory Management](#)
- [RSL Accessor Functions](#)
- [RSL Value Accessors](#)
- [RSL Display](#)
- [RSL Parsing](#)
- [List Functions](#)

## 2 Module Index

### 2.1 Modules

Here is a list of all modules:

<b>RSL Predicates</b>	<b><a href="#">2</a></b>
<b>RSL Constructors</b>	<b><a href="#">6</a></b>
<b>RSL Memory Management</b>	<b><a href="#">9</a></b>
<b>RSL Accessor Functions</b>	<b><a href="#">12</a></b>
<b>List Functions</b>	<b><a href="#">17</a></b>
<b>RSL Value Accessors</b>	<b><a href="#">17</a></b>
<b>RSL Display</b>	<b><a href="#">20</a></b>
<b>RSL Parsing</b>	<b><a href="#">21</a></b>

## 3 Module Documentation

### 3.1 RSL Predicates

The functions in this group return boolean values indicating whether an RSL syntax tree is of a particular type.

#### Functions

- int [globus\\_rsl\\_is\\_relation](#) (globus\_rsl\_t \*ast)
- int [globus\\_rsl\\_is\\_boolean](#) (globus\_rsl\_t \*ast)
- int [globus\\_rsl\\_is\\_relation\\_eq](#) (globus\_rsl\_t \*ast)
- int [globus\\_rsl\\_is\\_relation\\_lessthan](#) (globus\_rsl\_t \*ast)
- int [globus\\_rsl\\_is\\_relation\\_attribute\\_equal](#) (globus\_rsl\_t \*ast, char \*attribute)
- int [globus\\_rsl\\_is\\_boolean\\_and](#) (globus\_rsl\_t \*ast)
- int [globus\\_rsl\\_is\\_boolean\\_or](#) (globus\_rsl\_t \*ast)
- int [globus\\_rsl\\_is\\_boolean\\_multi](#) (globus\_rsl\_t \*ast)
- int [globus\\_rsl\\_value\\_is\\_literal](#) (globus\_rsl\_value\_t \*ast)
- int [globus\\_rsl\\_value\\_is\\_sequence](#) (globus\_rsl\_value\_t \*ast)
- int [globus\\_rsl\\_value\\_is\\_variable](#) (globus\_rsl\_value\_t \*ast)
- int [globus\\_rsl\\_value\\_is\\_concatenation](#) (globus\_rsl\_value\_t \*ast)

#### 3.1.1 Detailed Description

The functions in this group return boolean values indicating whether an RSL syntax tree is of a particular type.

#### 3.1.2 Function Documentation

##### 3.1.2.1 int `globus_rsl_is_relation ( globus_rsl_t * ast )`

RSL relation test.

The [globus\\_rsl\\_is\\_relation\(\)](#) function tests whether the the RSL pointed to by the *ast* parameter is a relation. The RSL syntax supports the following relation operations:

= Equal  
 != Not Equal  
 > Greater Than  
 >= Greater Than or Equal  
 < Less Than  
 <= Less Than or Equal  
 <= Less Than or Equal

Some examples of RSL relations are

```
"queue" = "debug"
"queue" != "slow"
"min_memory" > "1000"
"max_wall_time" >= "60"
"count" < "10"
"host_count" <= "5"
```

GRAM only supports equality relations.

#### Parameters

<i>ast</i>	Pointer to an RSL parse tree structure.
------------	---

#### Returns

The [globus\\_rsl\\_is\\_relation\(\)](#) function returns GLOBUS\_TRUE if the RSL parse tree pointed to by *ast* is a relation; otherwise, it returns GLOBUS\_FALSE.

#### 3.1.2.2 int globus\_rsl\_is\_boolean ( globus\_rsl\_t \* ast )

RSL boolean test.

The [globus\\_rsl\\_is\\_boolean\(\)](#) function tests whether the the RSL pointed to by the *ast* parameter is a boolean composition of other RSL parse trees. The syntactically understood boolean compositions are "&" (conjunction), "|" (disjunction), and "+" (multi-request). Some bexamples of RSL booleans are

```
& ( "queue" = "debug" ) ( "max_time" = "10000" )
| ( "count" = "1" ) ( "count" = "10" )
+ ( & ( "executable" = "1.exe" ) ) ( & ( "executable" = "2.exe" ) )
```

#### Parameters

<i>ast</i>	Pointer to an RSL parse tree structure.
------------	---

#### Returns

The [globus\\_rsl\\_is\\_boolean\(\)](#) function returns GLOBUS\_TRUE if the RSL parse tree pointed to by *ast* is a boolean composition; otherwise, it returns GLOBUS\_FALSE.

#### 3.1.2.3 int globus\_rsl\_is\_relation\_eq ( globus\_rsl\_t \* ast )

RSL equality operation test.

The [globus\\_rsl\\_is\\_relation\\_eq\(\)](#) function tests whether the the RSL pointed to by the *ast* parameter is an equality relation. An example of an equality relation is

```
"queue" = "debug"
```

#### Parameters

<i>ast</i>	Pointer to an RSL parse tree structure.
------------	---

#### Returns

The [globus\\_rsl\\_is\\_relation\\_eq\(\)](#) function returns GLOBUS\_TRUE if the RSL parse tree pointed to by *ast* is an equality relation; otherwise, it returns GLOBUS\_FALSE.

#### 3.1.2.4 int globus\_rsl\_is\_relation\_lessthan ( globus\_rsl\_t \* *ast* )

RSL less than operation test.

The [globus\\_rsl\\_is\\_relation\\_lessthan\(\)](#) function tests whether the the RSL pointed to by the *ast* parameter is a less-than relation. An example of a less-than relation is

```
"count" = "10"
```

#### Parameters

<i>ast</i>	Pointer to an RSL parse tree structure.
------------	---

#### Returns

The [globus\\_rsl\\_is\\_relation\\_lessthan\(\)](#) function returns GLOBUS\_TRUE if the RSL parse tree pointed to by *ast* is a less-than relation; otherwise, it returns GLOBUS\_FALSE.

#### 3.1.2.5 int globus\_rsl\_is\_relation\_attribute\_equal ( globus\_rsl\_t \* *ast*, char \* *attribute* )

RSL attribute name test.

The [globus\\_rsl\\_is\\_relation\\_attribute\\_equal\(\)](#) function tests whether the the RSL pointed to by the *ast* parameter is a relation with the attribute name which matches the string pointed to by the *attribute* parameter. This attribute name comparison is case-insensitive.

#### Parameters

<i>ast</i>	Pointer to an RSL parse tree structure.
<i>attribute</i>	Name of the attribute to test

#### Returns

The [globus\\_rsl\\_is\\_relation\\_attribute\\_equal\(\)](#) function returns GLOBUS\_TRUE if the RSL parse tree pointed to by *ast* is a relation and its attribute name matches the *attribute* parameter; otherwise, it returns GLOBUS\_FALSE.

#### 3.1.2.6 int globus\_rsl\_is\_boolean\_and ( globus\_rsl\_t \* *ast* )

RSL boolean and test.

The [globus\\_rsl\\_is\\_boolean\\_and\(\)](#) function tests whether the the RSL pointed to by the *ast* parameter is a boolean "and" composition of RSL trees. An example of a boolean and relation is

```
& ( "queue" = "debug" ) ( "executable" = "a.out" )
```

## Parameters

<i>ast</i>	Pointer to an RSL parse tree structure.
------------	---

## Returns

The [\*globus\\_rsl\\_is\\_boolean\\_and\(\)\*](#) function returns GLOBUS\_TRUE if the RSL parse tree pointed to by *ast* is a boolean and of RSL parse trees; otherwise, it returns GLOBUS\_FALSE.

### 3.1.2.7 int globus\_rsl\_is\_boolean\_or ( globus\_rsl\_t \* *ast* )

RSL boolean or test.

The [\*globus\\_rsl\\_is\\_boolean\\_or\(\)\*](#) function tests whether the the RSL pointed to by the *ast* parameter is a boolean "or" composition of RSL trees. An example of a boolean or relation is

```
| ( "count" = "2" ) ( "count" = "4" )
```

## Parameters

<i>ast</i>	Pointer to an RSL parse tree structure.
------------	---

## Returns

The [\*globus\\_rsl\\_is\\_boolean\\_or\(\)\*](#) function returns GLOBUS\_TRUE if the RSL parse tree pointed to by *ast* is a boolean and of RSL parse trees; otherwise, it returns GLOBUS\_FALSE.

### 3.1.2.8 int globus\_rsl\_is\_boolean\_multi ( globus\_rsl\_t \* *ast* )

RSL boolean multi test.

The [\*globus\\_rsl\\_is\\_boolean\\_multi\(\)\*](#) function tests whether the the RSL pointed to by the *ast* parameter is a boolean "multi-request" composition of RSL trees. An example of a boolean multi-request relation is

```
+ ( & ( "executable" = "exe.1" ) ( "count" = "2" ) )  
  ( & ( "executable" = " exe.2" ) ( "count" = "2" ) )
```

## Parameters

<i>ast</i>	Pointer to an RSL parse tree structure.
------------	---

## Returns

The [\*globus\\_rsl\\_is\\_boolean\\_multi\(\)\*](#) function returns GLOBUS\_TRUE if the RSL parse tree pointed to by *ast* is a boolean multi-request of RSL parse trees; otherwise, it returns GLOBUS\_FALSE.

### 3.1.2.9 int globus\_rsl\_value\_is\_literal ( globus\_rsl\_value\_t \* *ast* )

RSL literal string test.

The [\*globus\\_rsl\\_value\\_is\\_literal\(\)\*](#) function tests whether the the RSL value pointed to by the *ast* parameter is a literal string value. An example of a literal string is

```
"count"
```

## Parameters

<i>ast</i>	Pointer to an RSL value structure.
------------	------------------------------------

## Returns

The [\*globus\\_rsl\\_value\\_is\\_literal\(\)\*](#) function returns GLOBUS\_TRUE if the RSL value pointed to by *ast* is a literal

string value; otherwise, it returns GLOBUS\_FALSE.

#### 3.1.2.10 int globus\_rsl\_value\_is\_sequence ( globus\_rsl\_value\_t \* ast )

RSL value sequence test.

The [globus\\_rsl\\_value\\_is\\_sequence\(\)](#) function tests whether the RSL value pointed to by the *ast* parameter is a sequence of RSL values. An example of a sequence of values is

```
"1" "2" "3"
```

##### Parameters

<i>ast</i>	Pointer to an RSL value structure.
------------	------------------------------------

##### Returns

The [globus\\_rsl\\_value\\_is\\_sequence\(\)](#) function returns GLOBUS\_TRUE if the RSL value pointed to by *ast* is a value sequence; otherwise, it returns GLOBUS\_FALSE.

#### 3.1.2.11 int globus\_rsl\_value\_is\_variable ( globus\_rsl\_value\_t \* ast )

RSL value variable test.

The [globus\\_rsl\\_value\\_is\\_variable\(\)](#) function tests whether the RSL value pointed to by the *ast* parameter is a variable reference. RSL values. An example of a variable reference is

```
$( "GLOBUSRUN_GASS_URL" )
```

##### Parameters

<i>ast</i>	Pointer to an RSL value structure.
------------	------------------------------------

##### Returns

The [globus\\_rsl\\_value\\_is\\_variable\(\)](#) function returns GLOBUS\_TRUE if the RSL value pointed to by *ast* is a value sequence; otherwise, it returns GLOBUS\_FALSE.

#### 3.1.2.12 int globus\_rsl\_value\_is\_concatenation ( globus\_rsl\_value\_t \* ast )

RSL value concatenation test.

The [globus\\_rsl\\_value\\_is\\_concatenation\(\)](#) function tests whether the RSL value pointed to by the *ast* parameter is a concatenation of RSL values. An example of an RSL value concatenation is

```
$( "GLOBUSRUN_GASS_URL" ) # "/input"
```

##### Parameters

<i>ast</i>	Pointer to an RSL value structure.
------------	------------------------------------

##### Returns

The [globus\\_rsl\\_value\\_is\\_concatenation\(\)](#) function returns GLOBUS\_TRUE if the RSL value pointed to by *ast* is a value concatenation; otherwise, it returns GLOBUS\_FALSE.

## 3.2 RSL Constructors

## Functions

- `globus_rsl_t * globus_rsl_make_boolean` (int operator, globus\_list\_t \*children)
- `globus_rsl_t * globus_rsl_make_relation` (int operator, char \*attributename, globus\_rsl\_value\_t \*value\_sequence)
- `globus_rsl_value_t * globus_rsl_value_make_literal` (char \*string)
- `globus_rsl_value_t * globus_rsl_value_make_sequence` (globus\_list\_t \*value\_list)
- `globus_rsl_value_t * globus_rsl_value_make_variable` (globus\_rsl\_value\_t \*sequence)
- `globus_rsl_value_t * globus_rsl_value_make_concatenation` (globus\_rsl\_value\_t \*left\_value, globus\_rsl\_value\_t \*right\_value)

### 3.2.1 Function Documentation

#### 3.2.1.1 `globus_rsl_t* globus_rsl_make_boolean ( int operator, globus_list_t * children )`

RSL boolean constructor.

The [`globus\_rsl\_make\_boolean\(\)`](#) function creates a boolean composition of the RSL nodes in the list pointed to by *children*. The new RSL node which is returned contains a reference to the list, not a copy.

#### Parameters

<i>operator</i>	The boolean RSL operator to use to join the RSL parse tree list pointed to by the <i>children</i> parameter. This value must be one of GLOBUS_RSL_AND, GLOBUS_RSL_OR, GLOBUS_RSL_MULTIREQ in order to create a valid RSL tree.
<i>children</i>	Pointer to a list of RSL syntax trees to combine with the boolean operation described by the <i>operator</i> parameter.

#### Returns

The [`globus\_rsl\_make\_boolean\(\)`](#) function returns a new RSL parse tree node that contains a shallow reference to the list of values pointed to by the *children* parameter joined by the operator value in the *operator* parameter. If an error occurs, [`globus\_rsl\_make\_boolean\(\)`](#) returns NULL.

#### 3.2.1.2 `globus_rsl_t* globus_rsl_make_relation ( int operator, char * attributename, globus_rsl_value_t * value_sequence )`

RSL relation constructor.

The [`globus\_rsl\_make\_relation\(\)`](#) function creates a relation between the attribute named by the *attributename* parameter and the values pointed to by the *value\_sequence* list. The new RSL relation node which is returned contains a reference to the *attributename* and *value\_sequence* parameters, not a copy.

#### Parameters

<i>operator</i>	The RSL operator to use to relate the RSL attribute name pointed to by the <i>attributename</i> parameter and the values pointed to by the <i>value_sequence</i> parameter. This value must be one of GLOBUS_RSL_EQ, GLOBUS_RSL_NEQ, GLOBUS_RSL_GT, GLOBUS_RSL_GTEQ, GLOBUS_RSL_LT, or GLOBUS_RSL_LTEQ in order to create a valid RSL node.
<i>attributename</i>	Pointer to a string naming the attribute of the new RSL relation.
<i>value_sequence</i>	Pointer to a sequence of RSL values to use in the new RSL relation.

#### Returns

The [`globus\_rsl\_make\_relation\(\)`](#) function returns a new RSL parse tree node that contains a shallow reference to the attribute name pointed to by the *attributename* parameter and the RSL value sequence pointed to by the *value\_sequence* parameter. If an error occurs, [`globus\_rsl\_make\_relation\(\)`](#) returns NULL.



### 3.2.1.3 globus\_rsl\_value\_t\* globus\_rsl\_value\_make\_literal ( char \* *string* )

RSL literal constructor.

The [\*globus\\_rsl\\_value\\_make\\_literal\(\)\*](#) function creates a string literal RSL value node containing the value pointed to by the *string* parameter. The new RSL value node which is returned contains a reference to the *string* parameter, not a copy.

#### Parameters

<i>string</i>	The literal string to be used in the new value.
---------------	---

#### Returns

The [\*globus\\_rsl\\_value\\_make\\_literal\(\)\*](#) function returns a new RSL value node that contains a shallow reference to the string pointed to by the *string* parameter. If an error occurs, [\*globus\\_rsl\\_value\\_make\\_literal\(\)\*](#) returns NULL.

### 3.2.1.4 globus\_rsl\_value\_t\* globus\_rsl\_value\_make\_sequence ( globus\_list\_t \* *value\_list* )

RSL value sequence constructor.

The [\*globus\\_rsl\\_value\\_make\\_sequence\(\)\*](#) function creates a value sequence RSL node referring to the values pointed to by the *value\_list* parameter. The new node returned by this function contains a reference to the *value\_list* parameter, not a copy.

#### Parameters

<i>value_list</i>	A pointer to a list of globus_rsl_value_t pointers.
-------------------	---

#### Returns

The [\*globus\\_rsl\\_value\\_make\\_sequence\(\)\*](#) function returns a new RSL value node that contains a shallow reference to the list pointed to by the *value\_list* parameter. If an error occurs, [\*globus\\_rsl\\_value\\_make\\_sequence\(\)\*](#) returns NULL.

### 3.2.1.5 globus\_rsl\_value\_t\* globus\_rsl\_value\_make\_variable ( globus\_rsl\_value\_t \* *sequence* )

RSL variable reference constructor.

The [\*globus\\_rsl\\_value\\_make\\_variable\(\)\*](#) function creates a variable reference RSL node referring to the variable name contained in the value pointed to by *sequence* parameter. The new node returned by this function contains a reference to the *sequence* parameter, not a copy.

#### Parameters

<i>sequence</i>	A pointer to a RSL value sequence.
-----------------	------------------------------------

#### Returns

The [\*globus\\_rsl\\_value\\_make\\_variable\(\)\*](#) function returns a new RSL value node that contains a shallow reference to the value sequence pointed to by the *sequence* parameter. If an error occurs, [\*globus\\_rsl\\_value\\_make\\_variable\(\)\*](#) returns NULL.

### 3.2.1.6 globus\_rsl\_value\_t\* globus\_rsl\_value\_make\_concatenation ( globus\_rsl\_value\_t \* *left\_value*, globus\_rsl\_value\_t \* *right\_value* )

RSL concatenation constructor.

The [\*globus\\_rsl\\_value\\_make\\_concatenation\(\)\*](#) function creates a concatenation of the values pointed to by the *left\_* -

*value* and *right\_value* parameters. The new node returned by this function contains a reference to these parameters' values, not a copy.

#### Parameters

<i>left_value</i>	A pointer to a RSL value to act as the left side of the concatenation. This must be a string literal or variable reference.
<i>right_value</i>	A pointer to a RSL value to act as the right side of the concatenation. This must be a string literal or variable reference.

#### Returns

The [\*globus\\_rsl\\_value\\_make\\_concatenation\(\)\*](#) function returns a new RSL value node that contains a shallow reference to the values pointed to by the *left\_value* and *right\_value* parameters. If an error occurs, [\*globus\\_rsl\\_value\\_make\\_concatenation\(\)\*](#) returns NULL.

### 3.3 RSL Memory Management

#### Functions

- `globus_rsl_t * globus_rsl_copy_recursive (globus_rsl_t *ast_node)`
- `globus_rsl_value_t * globus_rsl_value_copy_recursive (globus_rsl_value_t *globus_rsl_value_ptr)`
- `int globus_rsl_value_free (globus_rsl_value_t *val)`
- `int globus_rsl_free (globus_rsl_t *ast_node)`
- `int globus_rsl_value_free_recursive (globus_rsl_value_t *globus_rsl_value_ptr)`
- `int globus_rsl_free_recursive (globus_rsl_t *ast_node)`
- `int globus_rsl_value_list_literal_replace (globus_list_t *value_list, char *string_value)`
- `int globus_rsl_value_eval (globus_rsl_value_t *ast_node, globus_symboltable_t *symbol_table, char **string_value, int rsl_substitution_flag)`
- `int globus_rsl_eval (globus_rsl_t *ast_node, globus_symboltable_t *symbol_table)`

#### 3.3.1 Function Documentation

##### 3.3.1.1 `globus_rsl_t* globus_rsl_copy_recursive ( globus_rsl_t * ast_node )`

Create a deep copy of an RSL syntax tree.

The [\*globus\\_rsl\\_copy\\_recursive\(\)\*](#) function performs a deep copy of the RSL syntax tree pointed to by the *ast\_node* parameter. All RSL nodes, value nodes, variable names, attributes, and literals will be copied to the return value.

#### Parameters

<i>ast_node</i>	An RSL syntax tree to copy.
-----------------	-----------------------------

#### Returns

The [\*globus\\_rsl\\_copy\\_recursive\(\)\*](#) function returns a copy of its input parameter that that can be used after the *ast\_node* and its values have been freed. If an error occurs, [\*globus\\_rsl\\_copy\\_recursive\(\)\*](#) returns NULL.

##### 3.3.1.2 `globus_rsl_value_t* globus_rsl_value_copy_recursive ( globus_rsl_value_t * globus_rsl_value_ptr )`

Create a deep copy of an RSL value.

The [\*globus\\_rsl\\_value\\_copy\\_recursive\(\)\*](#) function performs a deep copy of the RSL value pointed to by the *globus\_rsl\_value\_ptr* parameter. All variable names, attributes, literals, and value lists will be copied to the return value.

## Parameters

<i>globus_rsl_value_ptr</i>	A pointer to an RSL value to copy.
-----------------------------	------------------------------------

## Returns

The [\*globus\\_rsl\\_value\\_copy\\_recursive\(\)\*](#) function returns a copy of its input parameter that that can be used after the *globus\_rsl\_value\_ptr* and its values have been freed. If an error occurs, [\*globus\\_rsl\\_value\\_copy\\_recursive\(\)\*](#) returns NULL.

### 3.3.1.3 int globus\_rsl\_value\_free ( globus\_rsl\_value\_t \* val )

Free an RSL value node.

The [\*globus\\_rsl\\_value\\_free\(\)\*](#) function frees the RSL value pointed to by the *val* parameter. This only frees the RSL value node itself, and not any sequence or string values associated with that node.

## Parameters

<i>val</i>	The RSL value node to free.
------------	-----------------------------

## Returns

The [\*globus\\_rsl\\_value\\_free\(\)\*](#) function always returns GLOBUS\_SUCCESS.

### 3.3.1.4 int globus\_rsl\_free ( globus\_rsl\_t \* ast\_node )

Free an RSL syntax tree node.

The [\*globus\\_rsl\\_free\(\)\*](#) function frees the RSL syntax tree node pointed to by the *ast\_node* parameter. This only frees the RSL syntax tree node itself, and not any boolean operands, relation names, or values associated with the node.

## Parameters

<i>ast_node</i>	The RSL syntax tree node to free.
-----------------	-----------------------------------

## Returns

The [\*globus\\_rsl\\_value\\_free\(\)\*](#) function always returns GLOBUS\_SUCCESS.

### 3.3.1.5 int globus\_rsl\_value\_free\_recursive ( globus\_rsl\_value\_t \* globus\_rsl\_value\_ptr )

Free an RSL value and all its child nodes.

The [\*globus\\_rsl\\_free\\_recursive\(\)\*](#) function frees the RSL value node pointed to by the *globus\_rsl\_value\_ptr*, including all literal strings, variable names, and value sequences. Any pointers to these are no longer valid after [\*globus\\_rsl\\_value\\_free\\_recursive\(\)\*](#) returns.

## Parameters

<i>globus_rsl_value_ptr</i>	An RSL value node to free.
-----------------------------	----------------------------

## Returns

The [\*globus\\_rsl\\_value\\_free\\_recursive\(\)\*](#) function always returns GLOBUS\_SUCCESS.

### 3.3.1.6 int globus\_rsl\_free\_recursive ( globus\_rsl\_t \* *ast\_node* )

Free an RSL syntax tree and all its child nodes.

The [\*globus\\_rsl\\_free\\_recursive\(\)\*](#) function frees the RSL syntax tree pointed to by the *ast\_node* parameter, including all boolean operands, attribute names, and values. Any pointers to these are no longer valid after [\*globus\\_rsl\\_free\\_recursive\(\)\*](#) returns.

#### Parameters

<i>ast_node</i>	An RSL parse tree to free.
-----------------	----------------------------

#### Returns

The [\*globus\\_rsl\\_value\\_free\\_recursive\(\)\*](#) function always returns `GLOBUS_SUCCESS`.

### 3.3.1.7 int globus\_rsl\_value\_list\_literal\_replace ( globus\_list\_t \* *value\_list*, char \* *string\_value* )

Replace the first value in a value list with a literal.

The [\*globus\\_rsl\\_value\\_list\\_literal\\_replace\(\)\*](#) function replaces the first value in the list pointed to by the *value\_list* parameter with a new value node that is a literal string node pointing to the value of the *string\_value* parameter, freeing the old value.

#### Parameters

<i>value_list</i>	The RSL value list to modify by replacing its first element.
<i>string_value</i>	The new string value to use as a literal first element of the list pointed to by the <i>value_list</i> parameter.

#### Returns

Upon success, [\*globus\\_rsl\\_value\\_list\\_literal\\_replace\(\)\*](#) returns `GLOBUS_SUCCESS`, frees the current first value of *value\_list* and replaces it with a new literal string node pointing to the value of the *string\_value* parameter. If an error occurs, [\*globus\\_rsl\\_value\\_list\\_literal\\_replace\(\)\*](#) returns 1.

### 3.3.1.8 int globus\_rsl\_value\_eval ( globus\_rsl\_value\_t \* *ast\_node*, globus\_symboltable\_t \* *symbol\_table*, char \*\* *string\_value*, int *rsl\_substitution\_flag* )

Evaluate RSL substitutions in an RSL value node.

The [\*globus\\_rsl\\_value\\_eval\(\)\*](#) function modifies the value pointed to by its *ast\_node* parameter by replacing all RSL substitution variable reference nodes with the literal values those variables evaluate to based on the current scope of the symbol table pointed to by the *symbol\_table* parameter. It also combines string concatenations into literal string values. Any nodes which are replaced by this function are freed using [\*globus\\_rsl\\_value\\_free\\_recursive\(\)\*](#).

#### Parameters

<i>ast_node</i>	A pointer to the RSL value node to evaluate.
<i>symbol_table</i>	A symbol table containing current definitions of the RSL substitutions which can occur in this evaluation scope.
<i>string_value</i>	An output parameter which is set to point to the value of the string returned by evaluating the value node pointed to by <i>ast_node</i> if it evaluates to a literal value. list pointed to by the <i>value_list</i> parameter.
<i>rsl_substitution_flag</i>	A flag indicating whether the node pointed to by the <i>ast_node</i> parameter defines RSL substitution variables.

#### Returns

Upon success, [\*globus\\_rsl\\_value\\_eval\(\)\*](#) returns `GLOBUS_SUCCESS`, and replaces any RSL substitution val-

ues in the node pointed to by the *ast\_node* parameter. If the node evaluates to a single literal, the *string\_value* parameter is modified to point to the value of that literal. If an error occurs, *globus\_rsl\_value\_eval()* returns a non-zero value.

### 3.3.1.9 int globus\_rsl\_eval ( globus\_rsl\_t \* ast\_node, globus\_symboltable\_t \* symbol\_table )

Evaluate an RSL syntax tree.

The *globus\_rsl\_eval()* function modifies the RSL parse tree pointed to by its *ast\_node* parameter by replacing all RSL substitution variable reference nodes with the literal values those variables evaluate to based on the current scope of the symbol table pointed to by the *symbol\_table* parameter. It also combines string concatenations into literal string values. Any nodes which are replaced by this function are freed using *globus\_rsl\_value\_free\_recursive()*.

#### Parameters

<i>ast_node</i>	A pointer to the RSL syntax tree to evaluate.
<i>symbol_table</i>	A symbol table containing current definitions of the RSL substitutions which can occur in this evaluation scope.

#### Returns

Upon success, *globus\_rsl\_eval()* returns *GLOBUS\_SUCCESS*, and replaces all RSL substitution values and concatenations in *ast\_node* or its child nodes with the evaluated forms described above. If an error occurs, *globus\_rsl\_eval()* returns a non-zero value.

## 3.4 RSL Accessor Functions

#### Functions

- int *globus\_rsl\_boolean\_get\_operator* (globus\_rsl\_t \*ast\_node)
- globus\_list\_t \* *globus\_rsl\_boolean\_get\_operand\_list* (globus\_rsl\_t \*ast\_node)
- globus\_list\_t \*\* *globus\_rsl\_boolean\_get\_operand\_list\_ref* (globus\_rsl\_t \*boolean\_node)
- char \* *globus\_rsl\_relation\_get\_attribute* (globus\_rsl\_t \*ast\_node)
- int *globus\_rsl\_relation\_get\_operator* (globus\_rsl\_t \*ast\_node)
- globus\_rsl\_value\_t \* *globus\_rsl\_relation\_get\_value\_sequence* (globus\_rsl\_t \*ast\_node)
- globus\_rsl\_value\_t \* *globus\_rsl\_relation\_get\_single\_value* (globus\_rsl\_t \*ast\_node)
- char \* *globus\_rsl\_value\_literal\_get\_string* (globus\_rsl\_value\_t \*literal\_node)
- globus\_list\_t \* *globus\_rsl\_value\_sequence\_get\_value\_list* (globus\_rsl\_value\_t \*sequence\_node)
- globus\_rsl\_value\_t \* *globus\_rsl\_value\_variable\_get\_sequence* (globus\_rsl\_value\_t \*variable\_node)
- char \* *globus\_rsl\_value\_variable\_get\_name* (globus\_rsl\_value\_t \*variable\_node)
- char \* *globus\_rsl\_value\_variable\_get\_default* (globus\_rsl\_value\_t \*variable\_node)
- int *globus\_rsl\_value\_variable\_get\_size* (globus\_rsl\_value\_t \*variable\_node)
- globus\_rsl\_value\_t \* *globus\_rsl\_value\_concatenation\_get\_left* (globus\_rsl\_value\_t \*concatenation\_node)
- globus\_rsl\_value\_t \* *globus\_rsl\_value\_concatenation\_get\_right* (globus\_rsl\_value\_t \*concatenation\_node)
- globus\_list\_t \*\* *globus\_rsl\_value\_sequence\_get\_list\_ref* (globus\_rsl\_value\_t \*sequence\_node)

### 3.4.1 Function Documentation

#### 3.4.1.1 int globus\_rsl\_boolean\_get\_operator ( globus\_rsl\_t \* ast\_node )

Get the RSL operator used in a boolean RSL composition.

The *globus\_rsl\_boolean\_get\_operator()* function returns the operator that is used by the boolean RSL composition.

## Parameters

<i>ast_node</i>	The RSL syntax tree to inspect.
-----------------	---------------------------------

## Returns

Upon success, [globus\\_rsl\\_boolean\\_get\\_operator\(\)](#) returns one of GLOBUS\_RSL\_AND, GLOBUS\_RSL\_OR, GLOBUS\_RSL\_MULTIREQ. If an error occurs, [globus\\_rsl\\_boolean\\_get\\_operator\(\)](#) returns -1.

### 3.4.1.2 globus\_list\_t\* globus\_rsl\_boolean\_get\_operand\_list ( globus\_rsl\_t \* *ast\_node* )

Get the RSL operand list from a boolean RSL composition.

The [globus\\_rsl\\_boolean\\_get\\_operand\\_list\(\)](#) function returns the list of RSL syntax tree nodes that is joined by a boolean composition.

## Parameters

<i>ast_node</i>	The RSL syntax tree to inspect.
-----------------	---------------------------------

## Returns

Upon success, [globus\\_rsl\\_boolean\\_get\\_operand\\_list\(\)](#) returns a pointer to a list of RSL syntax tree nodes that are the operand of a boolean composition operation. If an error occurs, [globus\\_rsl\\_boolean\\_get\\_operand\\_list\(\)](#) returns NULL.

### 3.4.1.3 globus\_list\_t\*\* globus\_rsl\_boolean\_get\_operand\_list\_ref ( globus\_rsl\_t \* *boolean\_node* )

Get a reference to the RSL operand list from a boolean RSL composition.

The [globus\\_rsl\\_boolean\\_get\\_operand\\_list\\_ref\(\)](#) function returns a pointer to the list of RSL syntax tree nodes that is joined by a boolean composition. If this list is modified, then the value of boolean syntax tree is modified.

## Parameters

<i>boolean_node</i>	The RSL syntax tree to inspect.
---------------------	---------------------------------

## Returns

Upon success, [globus\\_rsl\\_boolean\\_get\\_operand\\_list\\_ref\(\)](#) returns a pointer to the list pointer in the RSL syntax tree data structure. This list can be modified to change the operands of the boolean operation. If an error occurs, [globus\\_rsl\\_boolean\\_get\\_operand\\_list\\_ref\(\)](#) returns NULL.

### 3.4.1.4 char\* globus\_rsl\_relation\_get\_attribute ( globus\_rsl\_t \* *ast\_node* )

Get an RSL relation attribute name.

The [globus\\_rsl\\_relation\\_get\\_attribute\(\)](#) function returns a pointer to the name of the attribute in an RSL relation. This return value is a shallow reference to the attribute name.

## Parameters

<i>ast_node</i>	The RSL relation node to inspect.
-----------------	-----------------------------------

## Returns

Upon success, [globus\\_rsl\\_relation\\_get\\_attribute\(\)](#) returns a pointer to the name of the attribute of the relation. If an error occurs, [globus\\_rsl\\_relation\\_get\\_attribute\(\)](#) returns NULL.

#### 3.4.1.5 `int globus_rsl_relation_get_operator ( globus_rsl_t * ast_node )`

Get an RSL relation operator.

The [`globus\_rsl\_relation\_get\_operator\(\)`](#) function returns the operation type represented by the RSL relation node pointed to by the `ast_node` parameter.

##### Parameters

<code>ast_node</code>	The RSL relation node to inspect.
-----------------------	-----------------------------------

##### Returns

Upon success, [`globus\_rsl\_relation\_get\_operator\(\)`](#) returns one of `GLOBUS_RSL_EQ`, `GLOBUS_RSL_NEQ`, `GLOBUS_RSL_GT`, `GLOBUS_RSL_GTEQ`, `GLOBUS_RSL_LT`, or `GLOBUS_RSL_LTEQ`. If an error occurs, [`globus\_rsl\_relation\_get\_operator\(\)`](#) returns -1.

#### 3.4.1.6 `globus_rsl_value_t* globus_rsl_relation_get_value_sequence ( globus_rsl_t * ast_node )`

Get the value of an RSL relation.

The [`globus\_rsl\_relation\_get\_value\_sequence\(\)`](#) function returns the value of an RSL relation node pointed to by the `ast_node` parameter.

##### Parameters

<code>ast_node</code>	The RSL relation node to inspect.
-----------------------	-----------------------------------

##### Returns

Upon success, [`globus\_rsl\_relation\_get\_value\_sequence\(\)`](#) returns the value sequence pointer in the RSL relation pointed to by the `ast_node` parameter. If an error occurs, [`globus\_rsl\_relation\_get\_value\_sequence\(\)`](#) returns NULL.

#### 3.4.1.7 `globus_rsl_value_t* globus_rsl_relation_get_single_value ( globus_rsl_t * ast_node )`

Get the single value of an RSL relation.

The [`globus\_rsl\_relation\_get\_single\_value\(\)`](#) function returns the value of an RSL relation node pointed to by the `ast_node` parameter if the value is a sequence of one value.

##### Parameters

<code>ast_node</code>	The RSL relation node to inspect.
-----------------------	-----------------------------------

##### Returns

Upon success, [`globus\_rsl\_relation\_get\_single\_value\(\)`](#) returns the value pointer at the head of the RSL relation pointed to by the `ast_node` parameter. If the value sequence has more than one value or the `ast_node` points to an RSL syntax tree that is not a relation, [`globus\_rsl\_relation\_get\_value\_sequence\(\)`](#) returns NULL.

#### 3.4.1.8 `char* globus_rsl_value_literal_get_string ( globus_rsl_value_t * literal_node )`

Get the string value of an RSL literal.

The [`globus\_rsl\_value\_literal\_get\_string\(\)`](#) function returns the string value of an RSL literal node pointed to by the `literal_node` parameter.

##### Parameters

<code>literal_node</code>	The RSL literal node to inspect.
---------------------------	----------------------------------

## Returns

Upon success, [globus\\_rsl\\_value\\_literal\\_get\\_string\(\)](#) returns a pointer to the string value of the literal pointed to by the *literal\_node* parameter. If the value is not a literal, [globus\\_rsl\\_value\\_literal\\_get\\_string\(\)](#) returns NULL.

### 3.4.1.9 globus\_list\_t\* globus\_rsl\_value\_sequence\_get\_value\_list ( globus\_rsl\_value\_t \* *sequence\_node* )

Get the value list from an RSL value sequence.

The [globus\\_rsl\\_value\\_sequence\\_get\\_value\\_list\(\)](#) function returns the list of *globus\_rsl\_value\_t* pointer values associated with the RSL value sequence pointed to by the *sequence\_node* parameter.

## Parameters

<i>sequence_node</i>	The RSL sequence node to inspect.
----------------------	-----------------------------------

## Returns

Upon success, [globus\\_rsl\\_value\\_sequence\\_get\\_value\\_list\(\)](#) returns a pointer to the list of values pointed to by the *sequence\_node* parameter. If the value is not a sequence, [globus\\_rsl\\_value\\_literal\\_get\\_string\(\)](#) returns NULL.

### 3.4.1.10 globus\_rsl\_value\_t\* globus\_rsl\_value\_variable\_get\_sequence ( globus\_rsl\_value\_t \* *variable\_node* )

Get the value sequence from an RSL variable reference.

The [globus\\_rsl\\_value\\_variable\\_get\\_sequence\(\)](#) function returns the sequence value associated with the RSL variable reference pointed to by the *variable\_node* parameter.

## Parameters

<i>variable_node</i>	The RSL variable node to inspect.
----------------------	-----------------------------------

## Returns

Upon success, [globus\\_rsl\\_value\\_variable\\_get\\_sequence\(\)](#) returns a pointer to the rsl value sequence pointed to by the *variable\_node* parameter. If the value is not a variable reference, [globus\\_rsl\\_value\\_variable\\_get\\_sequence\(\)](#) returns NULL.

### 3.4.1.11 char\* globus\_rsl\_value\_variable\_get\_name ( globus\_rsl\_value\_t \* *variable\_node* )

Get the name of an RSL variable reference.

The [globus\\_rsl\\_value\\_variable\\_get\\_name\(\)](#) function returns a pointer to the name of the RSL variable name pointed to by the *variable\_node* parameter.

## Parameters

<i>variable_node</i>	The RSL variable node to inspect.
----------------------	-----------------------------------

## Returns

Upon success, [globus\\_rsl\\_value\\_variable\\_get\\_name\(\)](#) returns a pointer to the string containing the name of the variable referenced by the *variable\_node* parameter. If the node is not a variable reference, [globus\\_rsl\\_value\\_variable\\_get\\_sequence\(\)](#) returns NULL.

### 3.4.1.12 char\* globus\_rsl\_value\_variable\_get\_default ( globus\_rsl\_value\_t \* *variable\_node* )

Get the default value of an RSL variable reference.



The [\*globus\\_rsl\\_value\\_variable\\_get\\_default\(\)\*](#) function returns a pointer to the default value of the RSL variable pointed to by the *variable\_node* parameter to use if the variable's name is not bound in the current evaluation context.

#### Parameters

<i>variable_node</i>	The RSL variable node to inspect.
----------------------	-----------------------------------

#### Returns

Upon success, [\*globus\\_rsl\\_value\\_variable\\_get\\_default\(\)\*](#) returns a pointer to the string containing the default value of the variable referenced by the *variable\_node* parameter. If the node is not a variable reference or no default value exists in the RSL node, [\*globus\\_rsl\\_value\\_variable\\_get\\_default\(\)\*](#) returns NULL.

#### 3.4.1.13 `int globus_rsl_value_variable_get_size ( globus_rsl_value_t * variable_node )`

Get the size of the value list within an RSL variable reference node.

The [\*globus\\_rsl\\_value\\_variable\\_get\\_size\(\)\*](#) function returns the number of nodes in the RSL variable reference node pointed to by the *variable\_node* parameter.

#### Parameters

<i>variable_node</i>	The RSL variable node to inspect.
----------------------	-----------------------------------

#### Returns

Upon success, [\*globus\\_rsl\\_value\\_variable\\_get\\_size\(\)\*](#) returns the list of values within a RSL variable reference, or -1 if the node pointed to by *variable\_node* is not a variable reference. If the return value is 1, then the variable has no default value included in the reference.

#### 3.4.1.14 `globus_rsl_value_t* globus_rsl_value_concatenation_get_left ( globus_rsl_value_t * concatenation_node )`

Get the left side of a concatenation value.

The [\*globus\\_rsl\\_value\\_concatenation\\_get\\_left\(\)\*](#) function returns the left side of an RSL value concatenation pointed to by the *concatenation\_node* parameter.

#### Parameters

<i>concatenation_node</i>	The RSL concatenation node to inspect.
---------------------------	--

#### Returns

Upon success, [\*globus\\_rsl\\_value\\_concatenation\\_get\\_left\(\)\*](#) returns a pointer to the left value of the concatenation values pointed to by the *concatenation\_node* parameter. If an error occurs, [\*globus\\_rsl\\_value\\_concatenation\\_get\\_left\(\)\*](#) returns NULL.

#### 3.4.1.15 `globus_rsl_value_t* globus_rsl_value_concatenation_get_right ( globus_rsl_value_t * concatenation_node )`

Get the right side of a concatenation value.

The [\*globus\\_rsl\\_value\\_concatenation\\_get\\_right\(\)\*](#) function returns the right side of an RSL value concatenation pointed to by the *concatenation\_node* parameter.

#### Parameters

<i>concatenation_node</i>	The RSL concatenation node to inspect.
---------------------------	--

## Returns

Upon success, [globus\\_rsl\\_value\\_concatenation\\_get\\_right\(\)](#) returns a pointer to the right value of the concatenation values pointed to by the *concatenation\_node* parameter. If an error occurs, [globus\\_rsl\\_value\\_concatenation\\_get\\_right\(\)](#) returns NULL.

### 3.4.1.16 globus\_list\_t\*\* globus\_rsl\_value\_sequence\_get\_list\_ref ( globus\_rsl\_value\_t \* *sequence\_node* )

Get a reference to the list of values in a sequence.

The [globus\\_rsl\\_value\\_sequence\\_get\\_list\\_ref\(\)](#) function returns a reference to the list of values in a value sequence. Any changes to the elements of this list will affect the *sequence\_node* parameter.

## Parameters

<i>sequence_node</i>	The RSL sequence node to inspect.
----------------------	-----------------------------------

## Returns

Upon success, [globus\\_rsl\\_value\\_sequence\\_get\\_list\\_ref\(\)](#) returns a pointer to the list of the *globus\_rsl\_value\_t* pointer values contained in the *sequence\_node* parameter. If an error occurs, [globus\\_rsl\\_value\\_sequence\\_get\\_list\\_ref\(\)](#) returns NULL.

## 3.5 List Functions

### Functions

- *globus\_list\_t* \* [globus\\_list\\_copy\\_reverse](#) (*globus\_list\_t* \**orig*)

### 3.5.1 Function Documentation

#### 3.5.1.1 globus\_list\_t\* globus\_list\_copy\_reverse ( globus\_list\_t \* *orig* )

Create a reverse-order copy of a list.

The [globus\\_list\\_copy\\_reverse\(\)](#) function creates and returns a copy of its input parameter, with the order of the list elements reversed. This copy is a shallow copy of list nodes, so both the list pointed to by *orig* and the returned list point to the same list element data.

## Parameters

<i>orig</i>	A pointer to the list to copy.
-------------	--------------------------------

## Returns

Upon success, [globus\\_list\\_copy\\_reverse\(\)](#) returns a new list containing the same elements as the list pointed to by *orig* in reverse order. If an error occurs, [globus\\_list\\_copy\\_reverse\(\)](#) returns NULL.

## 3.6 RSL Value Accessors

### Functions

- int [globus\\_rsl\\_value\\_concatenation\\_set\\_left](#) (*globus\_rsl\_value\_t* \**concatenation\_node*, *globus\_rsl\_value\_t* \**new\_left\_node*)
- int [globus\\_rsl\\_value\\_concatenation\\_set\\_right](#) (*globus\_rsl\_value\_t* \**concatenation\_node*, *globus\_rsl\_value\_t* \**new\_right\_node*)

- int [globus\\_rsl\\_value\\_list\\_param\\_get](#) (globus\_list\_t \*ast\_node\_list, int required\_type, char \*\*\*value, int \*value\_ctr)
- globus\_list\_t \* [globus\\_rsl\\_param\\_get\\_values](#) (globus\_rsl\_t \*ast\_node, char \*param)
- int [globus\\_rsl\\_param\\_get](#) (globus\_rsl\_t \*ast\_node, int param\_type, char \*param, char \*\*\*values)

### 3.6.1 Function Documentation

3.6.1.1 int [globus\\_rsl\\_value\\_concatenation\\_set\\_left](#) ( globus\_rsl\_value\_t \* *concatenation\_node*, globus\_rsl\_value\_t \* *new\_left\_node* )

Set the left-hand value of a concatenation.

The [globus\\_rsl\\_value\\_concatenation\\_set\\_left\(\)](#) sets the left hand side of a concatenation pointed to by *concatenation\_node* to the value pointed to by *new\_left\_node*. If there was any previous value to the left hand side of the concatenation, it is discarded but not freed.

#### Parameters

<i>concatenation_node</i>	A pointer to the RSL value concatenation node to modify.
<i>new_left_node</i>	A pointer to the new left hand side of the concatenation.

#### Returns

Upon success, [globus\\_rsl\\_value\\_concatenation\\_set\\_left\(\)](#) returns *GLOBUS\_SUCCESS* and modifies the value pointed to by the *concatenation\_node* parameter to use the value pointed to by the *new\_left\_node* parameter as its left hand side value. If an error occurs -1 is returned.

3.6.1.2 int [globus\\_rsl\\_value\\_concatenation\\_set\\_right](#) ( globus\_rsl\_value\_t \* *concatenation\_node*, globus\_rsl\_value\_t \* *new\_right\_node* )

Set the right-hand value of a concatenation.

The [globus\\_rsl\\_value\\_concatenation\\_set\\_right\(\)](#) sets the right-hand side of a concatenation pointed to by *concatenation\_node* to the value pointed to by *new\_right\_node*. If there was any previous value to the right-hand side of the concatenation, it is discarded but not freed.

#### Parameters

<i>concatenation_node</i>	A pointer to the RSL value concatenation node to modify.
<i>new_right_node</i>	A pointer to the new right hand side of the concatenation.

#### Returns

Upon success, [globus\\_rsl\\_value\\_concatenation\\_set\\_right\(\)](#) returns *GLOBUS\_SUCCESS* and modifies the value pointed to by the *concatenation\_node* parameter to use the value pointed to by the *new\_right\_node* parameter as its right hand side value. If an error occurs -1 is returned.

3.6.1.3 int [globus\\_rsl\\_value\\_list\\_param\\_get](#) ( globus\_list\_t \* *ast\_node\_list*, int *required\_type*, char \*\*\* *value*, int \* *value\_ctr* )

Get the values of an RSL value list.

The [globus\\_rsl\\_value\\_list\\_param\\_get\(\)](#) function copies pointers to literal string values or string pairs associated with the list of *globus\_rsl\_value\_t* pointers pointed to by the *ast\_node\_list* parameter to the output array pointed to by the *value* parameter. It modifies the value pointed to by the *value\_ctr* parameter to be the number of strings copied into the array.

## Parameters

<i>ast_node_list</i>	A pointer to a list of <code>globus_rsl_value_t</code> pointers whose values will be copied to the <i>value</i> parameter array.
<i>required_type</i>	A flag indicating whether the list is expected to contain literal strings or string pairs. This value may be one of <code>GLOBUS_RSL_VALUE_LITERAL</code> or <code>GLOBUS_RSL_VALUE_SEQUENCE</code> .
<i>value</i>	An output parameter pointing to an array of strings. This array must be at least as large as the number of elements in the list pointed to by <i>ast_node_list</i> .
<i>value_ctr</i>	An output parameter pointing to an integer that will be incremented for each string copied into the <i>value</i> array.

## Returns

Upon success, the [`globus\_rsl\_value\_list\_param\_get\(\)`](#) function returns `GLOBUS_SUCCESS` and modifies the values pointed to by the *value* and *value\_ctr* parameters as described above. If an error occurs, [`globus\_rsl\_value\_list\_param\_get\(\)`](#) returns a non-zero value.

### 3.6.1.4 `globus_list_t* globus_rsl_param_get_values ( globus_rsl_t * ast_node, char * param )`

Get the list of values for an RSL attribute.

The [`globus\_rsl\_param\_get\_values\(\)`](#) function searches the RSL parse tree pointed to by the *ast\_node* parameter and returns the value list that is bound to the attribute named by the *param* parameter.

## Parameters

<i>ast_node</i>	A pointer to an RSL syntax tree that will be searched. This may be a relation or boolean RSL string.
<i>param</i>	The name of the attribute to search for in the parse tree pointed to by the <i>ast_node</i> parameter.

## Returns

Upon success, the [`globus\_rsl\_param\_get\_values\(\)`](#) function returns a pointer to the list of values associated with the attribute named by *param* in the RSL parse tree pointed to by *ast\_node*. If an error occurs, [`globus\_rsl\_param\_get\_values\(\)`](#) returns `NULL`.

### 3.6.1.5 `int globus_rsl_param_get ( globus_rsl_t * ast_node, int param_type, char * param, char *** values )`

Get the value strings for an RSL attribute.

The [`globus\_rsl\_param\_get\(\)`](#) function searches the RSL parse tree pointed to by the *ast\_node* parameter and returns an array of pointers to the strings bound to the attribute named by the *param* parameter.

## Parameters

<i>ast_node</i>	A pointer to an RSL syntax tree that will be searched. This may be a relation or boolean RSL string.
<i>param_type</i>	A flag indicating what type of values are expected for the RSL attribute named by the <i>param</i> parameter. This flag value may be <code>GLOBUS_RSL_PARAM_SINGLE_LITERAL</code> , <code>GLOBUS_RSL_PARAM_MULTI_LITERAL</code> , or <code>GLOBUS_RSL_PARAM_SEQUENCE</code> .
<i>param</i>	A string pointing to the name of the RSL attribute to search for.
<i>values</i>	An output parameter pointing to an array of strings that will be allocated and contain pointers to the RSL value strings if they match the format specified by the <i>param_type</i> flag. The caller is responsible for freeing this array, but not the strings in the array.

## Returns

Upon success, the [`globus\_rsl\_param\_get\(\)`](#) function returns `GLOBUS_SUCCESS` and modifies the *values* parameter as described above. If an error occurs, [`globus\_rsl\_param\_get\(\)`](#) returns a non-zero value.

## 3.7 RSL Display

### Functions

- int [globus\\_rsl\\_value\\_print\\_recursive](#) (globus\_rsl\_value\_t \*globus\_rsl\_value\_ptr)
- char \* [globus\\_rsl\\_get\\_operator](#) (int my\_op)
- int [globus\\_rsl\\_print\\_recursive](#) (globus\_rsl\_t \*ast\_node)
- char \* [globus\\_rsl\\_unparse](#) (globus\_rsl\_t \*rsl\_spec)
- char \* [globus\\_rsl\\_value\\_unparse](#) (globus\_rsl\_value\_t \*rsl\_value)

### 3.7.1 Function Documentation

#### 3.7.1.1 int globus\_rsl\_value\_print\_recursive ( globus\_rsl\_value\_t \* *globus\_rsl\_value\_ptr* )

Print the value of a globus\_rsl\_value\_t to standard output.

The [globus\\_rsl\\_value\\_print\\_recursive\(\)](#) function prints a string representation of the RSL value node pointed to by the *globus\_rsl\_value\_ptr* parameter to standard output. This function is not reentrant.

#### Parameters

<i>globus_rsl_value_ptr</i>	A pointer to the RSL value to display.
-----------------------------	--

#### Returns

The [globus\\_rsl\\_value\\_print\\_recursive\(\)](#) function always returns *GLOBUS\_SUCCESS*.

#### 3.7.1.2 char\* globus\_rsl\_get\_operator ( int *my\_op* )

Get the string representation of an RSL operator.

The [globus\\_rsl\\_get\\_operator\(\)](#) function returns a pointer to a static string that represents the RSL operator passed in via the *my\_op* parameter. If the operator is not value, then [globus\\_rsl\\_get\\_operator\(\)](#) returns a pointer to the string "??"

#### Parameters

<i>my_op</i>	The RSL operator to return.
--------------	-----------------------------

#### Returns

The [globus\\_rsl\\_get\\_operator\(\)](#) function returns a pointer to the string representation of the *my\_op* parameter, or "??" if that value is not a value RSL operator.

#### 3.7.1.3 int globus\_rsl\_print\_recursive ( globus\_rsl\_t \* *ast\_node* )

Print the value of an RSL syntax tree to standard output.

The [globus\\_rsl\\_print\\_recursive\(\)](#) function prints a string representation of the RSL syntax tree pointed to by the *ast\_node* parameter to standard output. This function is not reentrant.

#### Parameters

<i>ast_node</i>	A pointer to the RSL syntax tree to display.
-----------------	--

## Returns

The [globus\\_rsl\\_print\\_recursive\(\)](#) function always returns `GLOBUS_SUCCESS`.

### 3.7.1.4 `char* globus_rsl_unparse ( globus_rsl_t * rsl_spec )`

Convert an RSL parse tree to a string.

The [globus\\_rsl\\_unparse\(\)](#) function returns a new string which can be parsed into the RSL syntax tree passed as the *rsl\_spec* parameter. The caller is responsible for freeing this string.

## Parameters

<i>rsl_spec</i>	A pointer to the RSL syntax tree to unparse.
-----------------	--

## Returns

Upon success, the [globus\\_rsl\\_unparse\(\)](#) function returns a new string which represents the RSL parse tree passed as the *rsl\_spec* parameter. If an error occurs, [globus\\_rsl\\_unparse\(\)](#) returns `NULL`.

### 3.7.1.5 `char* globus_rsl_value_unparse ( globus_rsl_value_t * rsl_value )`

Convert an RSL value pointer to a string.

The [globus\\_rsl\\_value\\_unparse\(\)](#) function returns a new string which can be parsed into the value of an RSL relation that has the same syntactic meaning as the *rsl\_value* parameter. The caller is responsible for freeing this string.

## Parameters

<i>rsl_value</i>	A pointer to the RSL value node to unparse.
------------------	---

## Returns

Upon success, the [globus\\_rsl\\_value\\_unparse\(\)](#) function returns a new string which represents the RSL value node passed as the *rsl\_value* parameter. If an error occurs, [globus\\_rsl\\_value\\_unparse\(\)](#) returns `NULL`.

## 3.8 RSL Parsing

### Functions

- `globus_rsl_t * globus_rsl_parse (char *buf)`

### 3.8.1 Function Documentation

#### 3.8.1.1 `globus_rsl_t* globus_rsl_parse ( char * buf )`

Parse an RSL string.

The [globus\\_rsl\\_parse\(\)](#) function parses the string pointed to by the *buf* parameter into an RSL syntax tree. The caller is responsible for freeing that tree by calling [globus\\_rsl\\_free\\_recursive\(\)](#).

## Parameters

<i>buf</i>	A NULL-terminated string that contains an RSL relation or boolean composition.
------------	--

## Returns

Upon success, the [globus\\_rsl\\_parse\(\)](#) function returns the parse tree generated by processing its input. If an error occurs, [globus\\_rsl\\_parse\(\)](#) returns `NULL`.

## Index

- globus\_list\_copy\_reverse
  - List Functions, [16](#)
- globus\_rsl\_boolean\_get\_operand\_list
  - RSL Accessor Functions, [12](#)
- globus\_rsl\_boolean\_get\_operand\_list\_ref
  - RSL Accessor Functions, [12](#)
- globus\_rsl\_boolean\_get\_operator
  - RSL Accessor Functions, [12](#)
- globus\_rsl\_copy\_recursive
  - RSL Memory Management, [9](#)
- globus\_rsl\_eval
  - RSL Memory Management, [11](#)
- globus\_rsl\_free
  - RSL Memory Management, [9](#)
- globus\_rsl\_free\_recursive
  - RSL Memory Management, [10](#)
- globus\_rsl\_get\_operator
  - RSL Display, [19](#)
- globus\_rsl\_is\_boolean
  - RSL Predicates, [3](#)
- globus\_rsl\_is\_boolean\_and
  - RSL Predicates, [4](#)
- globus\_rsl\_is\_boolean\_multi
  - RSL Predicates, [4](#)
- globus\_rsl\_is\_boolean\_or
  - RSL Predicates, [4](#)
- globus\_rsl\_is\_relation
  - RSL Predicates, [2](#)
- globus\_rsl\_is\_relation\_attribute\_equal
  - RSL Predicates, [3](#)
- globus\_rsl\_is\_relation\_eq
  - RSL Predicates, [3](#)
- globus\_rsl\_is\_relation\_lessthan
  - RSL Predicates, [3](#)
- globus\_rsl\_make\_boolean
  - RSL Constructors, [6](#)
- globus\_rsl\_make\_relation
  - RSL Constructors, [7](#)
- globus\_rsl\_param\_get
  - RSL Value Accessors, [19](#)
- globus\_rsl\_param\_get\_values
  - RSL Value Accessors, [18](#)
- globus\_rsl\_parse
  - RSL Parsing, [21](#)
- globus\_rsl\_print\_recursive
  - RSL Display, [20](#)
- globus\_rsl\_relation\_get\_attribute
  - RSL Accessor Functions, [13](#)
- globus\_rsl\_relation\_get\_operator
  - RSL Accessor Functions, [13](#)
- globus\_rsl\_relation\_get\_single\_value
  - RSL Accessor Functions, [13](#)
- globus\_rsl\_relation\_get\_value\_sequence
  - RSL Accessor Functions, [13](#)
- globus\_rsl\_unparse
  - RSL Display, [20](#)
- globus\_rsl\_value\_concatenation\_get\_left
  - RSL Accessor Functions, [15](#)
- globus\_rsl\_value\_concatenation\_get\_right
  - RSL Accessor Functions, [16](#)
- globus\_rsl\_value\_concatenation\_set\_left
  - RSL Value Accessors, [17](#)
- globus\_rsl\_value\_concatenation\_set\_right
  - RSL Value Accessors, [17](#)
- globus\_rsl\_value\_copy\_recursive
  - RSL Memory Management, [9](#)
- globus\_rsl\_value\_eval
  - RSL Memory Management, [10](#)
- globus\_rsl\_value\_free
  - RSL Memory Management, [9](#)
- globus\_rsl\_value\_free\_recursive
  - RSL Memory Management, [10](#)
- globus\_rsl\_value\_is\_concatenation
  - RSL Predicates, [6](#)
- globus\_rsl\_value\_is\_literal
  - RSL Predicates, [5](#)
- globus\_rsl\_value\_is\_sequence
  - RSL Predicates, [5](#)
- globus\_rsl\_value\_is\_variable
  - RSL Predicates, [5](#)
- globus\_rsl\_value\_list\_literal\_replace
  - RSL Memory Management, [10](#)
- globus\_rsl\_value\_list\_param\_get
  - RSL Value Accessors, [18](#)
- globus\_rsl\_value\_literal\_get\_string
  - RSL Accessor Functions, [14](#)
- globus\_rsl\_value\_make\_concatenation
  - RSL Constructors, [8](#)
- globus\_rsl\_value\_make\_literal
  - RSL Constructors, [7](#)
- globus\_rsl\_value\_make\_sequence
  - RSL Constructors, [7](#)
- globus\_rsl\_value\_make\_variable
  - RSL Constructors, [7](#)
- globus\_rsl\_value\_print\_recursive
  - RSL Display, [19](#)
- globus\_rsl\_value\_sequence\_get\_list\_ref
  - RSL Accessor Functions, [16](#)
- globus\_rsl\_value\_sequence\_get\_value\_list
  - RSL Accessor Functions, [14](#)
- globus\_rsl\_value\_unparse
  - RSL Display, [20](#)
- globus\_rsl\_value\_variable\_get\_default
  - RSL Accessor Functions, [15](#)

- globus\_rsl\_value\_variable\_get\_name
  - RSL Accessor Functions, [15](#)
- globus\_rsl\_value\_variable\_get\_sequence
  - RSL Accessor Functions, [14](#)
- globus\_rsl\_value\_variable\_get\_size
  - RSL Accessor Functions, [15](#)
- List Functions, [16](#)
  - globus\_list\_copy\_reverse, [16](#)
- RSL Accessor Functions, [11](#)
  - globus\_rsl\_boolean\_get\_operand\_list, [12](#)
  - globus\_rsl\_boolean\_get\_operand\_list\_ref, [12](#)
  - globus\_rsl\_boolean\_get\_operator, [12](#)
  - globus\_rsl\_relation\_get\_attribute, [13](#)
  - globus\_rsl\_relation\_get\_operator, [13](#)
  - globus\_rsl\_relation\_get\_single\_value, [13](#)
  - globus\_rsl\_relation\_get\_value\_sequence, [13](#)
  - globus\_rsl\_value\_concatenation\_get\_left, [15](#)
  - globus\_rsl\_value\_concatenation\_get\_right, [16](#)
  - globus\_rsl\_value\_literal\_get\_string, [14](#)
  - globus\_rsl\_value\_sequence\_get\_list\_ref, [16](#)
  - globus\_rsl\_value\_sequence\_get\_value\_list, [14](#)
  - globus\_rsl\_value\_variable\_get\_default, [15](#)
  - globus\_rsl\_value\_variable\_get\_name, [15](#)
  - globus\_rsl\_value\_variable\_get\_sequence, [14](#)
  - globus\_rsl\_value\_variable\_get\_size, [15](#)
- RSL Constructors, [6](#)
  - globus\_rsl\_make\_boolean, [6](#)
  - globus\_rsl\_make\_relation, [7](#)
  - globus\_rsl\_value\_make\_concatenation, [8](#)
  - globus\_rsl\_value\_make\_literal, [7](#)
  - globus\_rsl\_value\_make\_sequence, [7](#)
  - globus\_rsl\_value\_make\_variable, [7](#)
- RSL Display, [19](#)
  - globus\_rsl\_get\_operator, [19](#)
  - globus\_rsl\_print\_recursive, [20](#)
  - globus\_rsl\_unparse, [20](#)
  - globus\_rsl\_value\_print\_recursive, [19](#)
  - globus\_rsl\_value\_unparse, [20](#)
- RSL Memory Management, [8](#)
  - globus\_rsl\_copy\_recursive, [9](#)
  - globus\_rsl\_eval, [11](#)
  - globus\_rsl\_free, [9](#)
  - globus\_rsl\_free\_recursive, [10](#)
  - globus\_rsl\_value\_copy\_recursive, [9](#)
  - globus\_rsl\_value\_eval, [10](#)
  - globus\_rsl\_value\_free, [9](#)
  - globus\_rsl\_value\_free\_recursive, [10](#)
  - globus\_rsl\_value\_list\_literal\_replace, [10](#)
- RSL Parsing, [21](#)
  - globus\_rsl\_parse, [21](#)
- RSL Predicates, [1](#)
  - globus\_rsl\_is\_boolean, [3](#)
  - globus\_rsl\_is\_boolean\_and, [4](#)
  - globus\_rsl\_is\_boolean\_multi, [4](#)
  - globus\_rsl\_is\_boolean\_or, [4](#)
  - globus\_rsl\_is\_relation, [2](#)
  - globus\_rsl\_is\_relation\_attribute\_equal, [3](#)
  - globus\_rsl\_is\_relation\_eq, [3](#)
  - globus\_rsl\_is\_relation\_lessthan, [3](#)
  - globus\_rsl\_value\_is\_concatenation, [6](#)
  - globus\_rsl\_value\_is\_literal, [5](#)
  - globus\_rsl\_value\_is\_sequence, [5](#)
  - globus\_rsl\_value\_is\_variable, [5](#)
- RSL Value Accessors, [17](#)
  - globus\_rsl\_param\_get, [19](#)
  - globus\_rsl\_param\_get\_values, [18](#)
  - globus\_rsl\_value\_concatenation\_set\_left, [17](#)
  - globus\_rsl\_value\_concatenation\_set\_right, [17](#)
  - globus\_rsl\_value\_list\_param\_get, [18](#)