

globus rsl assist  
2.2

Generated by Doxygen 1.7.4

Fri Jun 17 2011 06:18:36

# Contents

<b>1</b>	<b><a href="#">RSL Helper Functions</a></b>	<b>1</b>
<b>2</b>	<b><a href="#">Module Index</a></b>	<b>1</b>
2.1	<a href="#">Modules</a> . . . . .	1
<b>3</b>	<b><a href="#">Module Documentation</a></b>	<b>1</b>
3.1	<a href="#">RSL Helper Functions</a> . . . . .	1
3.1.1	<a href="#">Detailed Description</a> . . . . .	1
3.1.2	<a href="#">Function Documentation</a> . . . . .	1

## 1 RSL Helper Functions

[RSL Helper Functions](#)

## 2 Module Index

### 2.1 Modules

Here is a list of all modules:

<b>RSL Helper Functions</b>	<b>1</b>
-----------------------------	----------

## 3 Module Documentation

### 3.1 RSL Helper Functions

#### Functions

- int [globus\\_rsl\\_assist\\_attributes\\_canonicalize](#) (globus\_rsl\_t \*rsl)
- void [globus\\_rsl\\_assist\\_string\\_canonicalize](#) (char \*ptr)

#### 3.1.1 Detailed Description

The rsl\_assist library provide a set of functions to canonicalize RSL parse trees or strings.

#### 3.1.2 Function Documentation

##### 3.1.2.1 int globus\_rsl\_assist\_attributes\_canonicalize ( globus\_rsl\_t \* rsl )

Canonicalize all attribute names in an RSL parse tree.

The [globus\\_rsl\\_assist\\_attributes\\_canonicalize\(\)](#) function performs an in-place canonicalization of the RSL parse tree pointed to by its *rsl* parameter. All relation attribute names will be changed so that they lower-case, with all internal underscore characters removed.

### Parameters

<i>rs/</i>	Pointer to the RSL parse tree to canonicalize.
------------	--

### Returns

If [globus\\_rsl\\_assist\\_attributes\\_canonicalize\(\)](#) is successful, it will ensure that all attribute names in the given RSL will be in canonical form and return GLOBUS\_SUCCESS. If an error occurs, it will return GLOBUS\_FAILURE.

### Return values

<i>GLOBUS_SUCCESS</i>	Success
<i>GLOBUS_FAILURE</i>	Failure

### 3.1.2.2 void globus\_rsl\_assist\_string\_canonicalize ( char \* *ptr* )

Canonicalize an attribute name.

The [globus\\_rsl\\_assist\\_string\\_canonicalize\(\)](#) function modifies the NULL-terminated string pointed to by its *ptr* parameter so that it is in canonical form. The canonical form is all lower-case with all underscore characters removed.

### Parameters

<i>ptr</i>	Pointer to the RSL string to modify in place.
------------	---

### Returns

void

## Index

globus\_rsl\_assist\_attributes\_canonicalize

RSL Helper Functions, [1](#)

globus\_rsl\_assist\_string\_canonicalize

RSL Helper Functions, [2](#)

RSL Helper Functions, [1](#)

globus\_rsl\_assist\_attributes\_canonicalize, [1](#)

globus\_rsl\_assist\_string\_canonicalize, [2](#)